




## Combo Tridem Chassis 20'-40', Spring-ride



### SPECIFICATIONS

<b>Overall Length</b>	41' extended (carries one loaded 20' or 40' or two empty 20' ISO containers)
<b>Overall Width</b>	96"
<b>Deck Height</b>	48" (rear)
<b>Coupler Height</b>	46.5"
<b>Kingpin Setting</b>	17.5"
<b>Weight</b>	10,400 lbs. +/- 3%
<b>GVWR</b>	40' is 83,000 lbs.; 20' is 76,000 lbs.
<b>Suspension</b>	Tridem axle, 2-position, sliding spring-ride suspension
<b>Axles</b>	1/2" axle wall, 22,500 lb. capacity with synthetic wheel-end lubricant
<b>Tires</b>	255/70R22.5 radial tires for tridem axle application
<b>Wheels</b>	8.25 x 22.5 hub-piloted wheels
<b>Brakes</b>	16-1/2" x 7" x 3/4" s-cam, quick-change extended life brake shoes
<b>ABS</b>	4 sensor / 2 modulator-valve system
<b>Upper Coupler</b>	AAR certified coupler with 1/4" pick-up plate. Interior coupler surfaces sealed with corrosion resistant coating
<b>Main Frame</b>	One piece, high strength steel I-beams
<b>Crossmembers</b>	3/16" fabricated Z-sections
<b>Bolsters</b>	Heavy-duty with retractable front and rear twist locks, swing down center locks
<b>Twist Locks</b>	(12) Cast steel design to meet ISO standards and requirements
<b>Landing Gear</b>	AAR certified, self-lubricating 2-speed landing gear with internal gearbox and low-profile sand shoes
<b>Lights &amp; Wiring</b>	LED lights with a fully sealed wiring harness and internal ground
<b>Electrical Connections</b>	7-way ATA plug with no circuit breakers
<b>Air Connections</b>	Fixed gladhands

Trailer specification features may vary based upon manufacturer model year, trailer type and location. Equipment is subject to availability at each location.