



# 50-Ton Lowboy 50', Air-ride, Hydraulic Removable Gooseneck



## FEATURES AND BENEFITS

All XTRA Lease trailers are spec'd to resist damage, ease loading and reduce maintenance costs. Here are just a few of the top features and benefits for this spec.

### Loader Friendly

- Adjustable Gooseneck Heights
- Outriggers And Lashing Rings for Cargo Control
- Folding Load Ramps

### Extended Maintenance

- Extended Life Brake Linings
- Synthetic Grease Wheel Ends
- Self-Lubricating Landing Gear

## SPECIFICATIONS

<b>Overall Length</b>	50'
<b>Overall Width</b>	102"
<b>Deck Height</b>	20" main deck (loaded), 39" rear deck (6" ground clearance loaded)
<b>Deck Length</b>	24' center deck (clear)
<b>Coupler Height</b>	48"
<b>Kingpin Setting</b>	16"
<b>Weight</b>	18,800 lbs. +/- 3%
<b>Suspension</b>	Fixed position tridem axles, Air-Ride suspension, including automatic and manual raising and lowering system. Does not meet California bridge formula.
<b>Axles</b>	5/8" axle wall, 25,000 lb. capacity with synthetic wheel-end lubricant. Rear axle set approximately 46'4" from the centerline of the kingpin to the centerline of the rear axle.
<b>Tires</b>	255/70R 22.5 premium radial tires
<b>Wheels</b>	8.25" x 22.5" steel hub-piloted wheels
<b>Brakes</b>	16-1/2" x 7" x 3/4" s-cam, quick-change extended- life brake shoes
<b>ABS</b>	4 sensor / 2 modulator-valve system
<b>Gooseneck</b>	Hydraulic removable gooseneck with adjustable ride height. Powered by on-board gasoline engine
<b>Main Frame</b>	Fabricated high-tensile steel main beams
<b>Side Rails</b>	12" steel I-beams
<b>Crossmembers</b>	8" steel I-beam crossmembers on 24" centers



## 50-Ton Lowboy 50', Air-ride, Hydraulic Removable Gooseneck

### SPECIFICATIONS

<b>Bolsters</b>	Heavy-duty bolsters with chain slots and flag holders behind each axle
<b>Cargo Control</b>	10 lash ring pairs & 12 outrigger pairs
<b>Floor</b>	1-1/2" apitong floor with 12" outriggers on both sides. 2 heavy-duty folding ramps at front of main deck
<b>Lights &amp; Wiring</b>	Sealed-beam lights with a fully sealed wiring harness and internal ground
<b>Electrical Connections</b>	7-way ATA plug with no circuit breakers
<b>Air Connections</b>	Stationary gladhands

Trailer specification features may vary based upon manufacturer model year, trailer type and location. Equipment is subject to availability at each location.