



55-Ton Lowboy 50', Air-ride, Hydraulic Removable Gooseneck



FEATURES AND BENEFITS

All XTRA Lease trailers are spec'd to resist damage, ease loading and reduce maintenance costs. Here are just a few of the top features and benefits for this spec.

Loader Friendly

- Adjustable Gooseneck Heights
- Outriggers And Lashing Rings for Cargo Control
- Folding Load Ramps

Extended Maintenance

- Extended Life Brake Linings
- Synthetic Grease Wheel Ends
- Self-Lubricating Landing Gear

SPECIFICATIONS

Overall Length	52' 1"
Overall Width	102"
Deck Height	22" main deck (loaded); approx. 39.5" rear deck
Deck Length	26' center deck (clear); 14' 2" rear deck length
Gooseneck Length	11' 11"
Coupler Height	Five-position adjustable from 48" – 56" (loaded)
Kingpin Setting	16"
Capacity	55 tons in 12' area of center load deck
Weight	22,350 lbs. +/- 3%
Suspension	Air-Ride suspension, including automatic and manual raising and lowering system. Third axle has left axle kit installed.
Axles	Two heavy-duty axles; 5/8" axle wall, 25,000 lb. capacity with synthetic wheel-end lubricant.
Tires	255/70R 22.5 premium radial tires
Wheels	8.25" x 22.5" steel hub-piloted wheels
Brakes	16-1/2" x 7" x 3/4" s-cam, quick-change extended- life brake shoes
ABS	4 sensor / 2 modulator-valve system
Gooseneck	Hydraulic removable gooseneck with adjustable ride height. Powered by on-board gasoline engine. One 4" x 10" double acting support cylinder and 34" wide crossbar. Vertical travel of 16" up and 20" down
Main Frame	Fabricated high-tensile steel main beams



55-Ton Lowboy 50', Air-ride, Hydraulic Removable Gooseneck

SPECIFICATIONS

Side Rails	12" steel I-beams
Crossmembers	10" steel I-beam crossmembers on 24" centers
Bolsters	Heavy-duty bolsters with chain slots and flag holders behind each axle
Cargo Control	14 lash ring pairs & 13 outrigger pairs
Floor	1-1/2" apitong floor with two heavy-duty folding ramps at front of main deck
Lights & Wiring	Sealed-beam lights with a fully sealed wiring harness and internal ground
Electrical Connections	7-way ATA plug with no circuit breakers
Air Connections	Stationary gladhands

Trailer specification features may vary based upon manufacturer model year, trailer type and location.
Equipment is subject to availability at each location.