

# **Double-Drop Extendable Flatbed**

48', Air-ride

# **FEATURES AND BENEFITS**

All XTRA Lease trailers are spec'd to resist damage, ease loading and reduce maintenance costs. Here are just a few of the top features and benefits for this spec.

# **Loader Friendly**

# • Lashing Rings For Cargo Control

#### **Extended Maintenance**

- Extended Life Brake Linings
- Synthetic Grease Wheel Ends
- Self-Lubricating Landing Gear

# **Damage Resistant**

 Heavy Duty Main Beams And Side Rails

# **SPECIFICATIONS**

| Overall Length     | 48' to 69' (Extends in 5' Increments)  |
|--------------------|--|
| Overall Width      | 102"   |
| Deck Height        | 20" center deck, 41" rear deck   |
| Center Deck Length | 29' – 50'; stops on five 12-inch increments  |
| Coupler Height     | 50"  |
| Kingpin Setting    | 16"  |
| Weight             | 20,100 lbs. +/- 3%   |
| Suspension         | Fixed position tandem axles with Air-Ride suspension. Airbags equipped with self-regulating height control valve and manual dump valve |
| Axles              | 5/8" axle wall, 25,000 lb. capacity with synthetic wheel-end lubricant   |
| Tires              | 255/70R 22.5 premium radial tires  |
| Wheels             | 8.25" x 22.5" steel hub-piloted wheels   |
| Brakes             | 16-1/2" x 7" x 3/4" s-cam, quick-change, extended life brake shoes   |
| ABS                | 2 sensor / 1 modulator-valve system  |
| Upper Coupler      | AAR certified coupler with 1/4" pick-up and 5th-wheel plates. Interior coupler surfaces sealed with corrosion resistant coating        |
| Main Frame         | Fabricated high-tensile steel main beams, air operated stops on 5' increments  |
| Side Rails         | 6" structural steel channel on front deck, 8" on center deck   |
| Crossmembers       | 4" steel crossmembers on 18" centers under front deck, 8" steel crossmembers on 24" centers on center deck                             |
| Landing Gear       | AAR certified, self-lubricating 2-speed landing gear with internal gearbox and cushion sand shoes                                      |
|                    |  |



# Double-Drop Extendable Flatbed 48', Air-ride

# **SPECIFICATIONS**

| Cargo Control          | Nine pair of lashing rings  |
|------------------------|---|
| Floor                  | 1-1/8" apitong floor  |
| Bulkhead               | 48" Flat, Removable Bulkhead  |
| Lights & Wiring        | Sealed-beam lights with a fully sealed wiring harness and internal ground |
| Electrical Connections | 7-way ATA plug with no circuit breakers                                   |
| Air Connections        | Stationary gladhands mounted on roadside                                  |

Trailer specification features may vary based upon manufacturer, model year, trailer type and location. Equipment is subject to availability at each location.