



Single-Drop, Spread-axle Flatbed 53', Air-ride



FEATURES AND BENEFITS

All XTRA Lease trailers are spec'd to resist damage, ease loading and reduce maintenance costs. Here are just a few of the top features and benefits for this spec.

Loader Friendly

- Cargo Control Combination Winches
- Spread Axles for increased Payload Capacity

Extended Maintenance

- Extended Life Brake Linings
- Synthetic Grease Wheel Ends
- Self-Lubricating Landing Gear

Damage Resistant

- Integrated Aluminum Side Rub Rails

SPECIFICATIONS

| | |
|------------------------|---|
| Overall Length | 53' |
| Overall Width | 102" |
| Deck Height | 61.25" front deck, 40" rear deck (loaded) |
| Deck Length | 10' front deck, 43' rear deck (closed) |
| Coupler Height | 49" |
| Kingpin Setting | 24" |
| Weight | 10,980 lbs. (including the bulkhead, 275 lbs.) +/- 3% |
| Suspension | Fixed position tandem axles with Air-Ride suspension. Airbags equipped with self-regulating height control valve, electric dump valve on rear axle wired to auxiliary socket, mounted at nose. Automatic gladhand dump valve dumps air when parking brake is set. |
| Axles | 5/8" axle wall, 23,000 lb. capacity with synthetic wheel-end lubricant |
| Tires | 255/70R 22.5 radial tires for spread axle application |
| Wheels | 8.25" x 22.5" steel hub-piloted wheels |
| Brakes | 16-1/2" x 7" x 3/4" s-cam, quick-change, extended life brake shoes |
| ABS | 2 sensor / 1 modulator-valve system |
| Upper Coupler | AAR certified coupler with 1/4" pick-up and 5th-wheel plates. Interior coupler surfaces sealed with corrosion resistant coating |
| Main Frame | Fabricated high-tensile steel main beams, air operated stops on 5' increments |
| Side Rails | Aluminum with integrated routed stake packets |
| Rub Rails | Integrated into side rail |



Single-Drop, Spread-axle Flatbed 53', Air-ride

SPECIFICATIONS

| | |
|-------------------------------|---|
| Stake Pockets | Internal aluminum stake pockets on 24" centers. Full length both sides, front and rear. Two load securement openings between packets. |
| Crossmembers | 4" steel I-beam crossmembers on 12" centers |
| Landing Gear | AAR certified, self-lubricating 2-speed landing gear with internal gearbox and cushion sand shoes |
| Cargo Control | Roadside combination winches with sliding rope hook/winch. Strap hook retainers opposite of winches. |
| Floor | 1-1/8" aluminum floor with four apitong nailer strips |
| Bulkhead | 48" flat, removable aluminum bulkhead |
| Lights & Wiring | Sealed-beam lights with a fully sealed wiring harness and internal ground |
| Electrical Connections | 7-way ATA plug with no circuit breakers |
| Air Connections | Stationary gladhands mounted flush on roadside |

Trailer specification features may vary based upon manufacturer, model year, trailer type and location. Equipment is subject to availability at each location.