




Extendable Straight-frame Flatbed 48'-80', Spring-ride



FEATURES AND BENEFITS

All XTRA Lease flatbeds are spec'd to resist damage, ease loading and reduce maintenance costs. Here are just a few of the top features and benefits for this spec.

Loader Friendly

- Cargo Control combination winches

Extended Maintenance

- Extended Life Brake Linings
- Synthetic Grease Wheel Ends
- Self-Lubricating Landing Gear

Damage Resistant

- Heavy Duty Rub Rails
- No Air Fittings at 5' Stops

SPECIFICATIONS

Overall Length	48' to 80' (Extends in 5' Increments)
Overall Width	102"
Deck Height	60"
Deck Length	11' front deck, 37' rear deck (closed)
Coupler Height	49"
Kingpin Setting	24"
Weight	16,390 lbs. +/- 3% (bulkhead + 275 lbs.)
Suspension	Variable position tandem axles with spring-ride suspension.
Axles	5/8" axle wall, 25,000 lb. capacity with synthetic grease wheel-end lubricant
Tires	295/75R 22.5 radial tires
Wheels	8.25" x 22.5" steel hub-piloted wheels
Brakes	16-1/2" x 7" x 7/8" s-cam, quick-change, extended life brake shoes
ABS	2 sensor / 1 modulator-valve system
Upper Coupler	AAR certified coupler with 1/4" pick-up and 5th-wheel plates. Interior coupler surfaces sealed with corrosion resistant coating
Main Frame	Fabricated high-tensile steel main beams, air operated stops on 5' increments
Side Rails	6" structural steel channel
Rub Rails	2.5" wide rub rails. Full length both sides, front and rear, reinforced with pipe spools.
Stake Pockets	3/16" thick, external steel stake pockets on 24" centers. Full length both sides, front and rear.



Extendable Straight-frame Flatbed 48'-80', Spring-ride

SPECIFICATIONS

Crossmembers	4" steel I-beam crossmembers on 12" centers
Landing Gear	AAR certified, self-lubricating 2-speed landing gear with internal gearbox and cushion sand shoes
Cargo Control	Combination winches and "c" type rope-hooks
Floor	1-1/8" apitong floor
Bulkhead	48" flat, removable bulkhead
Lights & Wiring	Sealed-beam lights with a fully sealed wiring harness and internal ground
Electrical Connections	7-way ATA plug with no circuit breakers
Air Connections	Stationary gladhands mounted on roadside

Trailer specification features may vary based upon manufacturer, model year, trailer type and location.
Equipment is subject to availability at each location.